DDCTM SERIES

The DDC features an exclusive, patented virtual dial interface that guides a user through simple programming functions. Although compact in size, several large features are packed into the DDC – making it extremely affordable for any residential application.



Toro exclusive "Digital Dial" Technology

Simulates the simplicity of a mechanical dial

3 independent programs

Easily identified within "digital dial" interface

Water Budget: 0 to 200% in 10% increments

Monthly preset option — ideal for system start-up or shutdown in advance

Self-diagnostic circuit breaker

Identifies irrigation faults

Multi-lingual Display

User selectable multi-language overlays



Additional Features

- ✓ 4, 6 and 8 Station
- ✓ 3 Start Times per Program
- ✓ 365 Day Calendar
- 1 to 240 minute run times with delay between stations
- Multiple watering days options:
 - 7 day calendar
 - 14 day interval
 - Odd/Even day watering, with 31st day exclusion
- Arm-Chair programming with 9-volt battery power source
- Key locking outdoor cabinet provides vandel resistance



SPECIFICATIONS

Technical

- Large LCD display
- Manual programs start for programs stored in controller memory
- Built-in Rain delay with sensor terminal hookups
- Programmable Master Valve
- Convenient program review feature
- Program retention with on board coin battery
- Default program if loss of power occurs
- Quick reference card for programming assistance
- CE, EMC, C-Tick, UL and cUL approved
- Accepts Toro TWRS or TWRFS wireless rain/freeze sensor
- Program review feature
- Self diagnostic circuit breaker

Electrical

- •Input power: 220 VAC, 50 Hz (Plug-in transformer, CE Mark)
- 0.50 amps (60 W) maximum
- Station Output Power: 24 VAC
 - 0.25 amps (6 VA) per station maximum
- 0.25 amps (6 VA) pump start/master valve
- 0.50 amps (12 VA) total load

Dimensions

- · Indoor:
- 127mm x 146mm x 40mm (H x W x D) - Weight without 9-volt battery: 280 grams 500mA class 2 transformer
- Outdoor:
 - 20mm x 178mm x 89mm (H x W x D)
 - Weight without 9-volt battery:1,14 Kg

Warranty

• Two years

WATER MANAGEMENT HIGHLIGHT

MONTHLY SEASON ADJUST

Irrigation run times can be set and then pre-adjusted for entire year from 0-200% in 10% increments by month. With easy adjusting for seasonal watering, water savings is enhanced for all around intelligent programming.



| DDC SERIES 220 VAC MODEL LIST | | | | |
|----------------------------------|---|--|--|--|
| Model | Description | | | |
| INDOOR DIGITAL DIAL CONTROLLERS | | | | |
| DDC-4-220 | 4-Station, Indoor, 220 VAC Plug-In Transformer, Exclusive Digital Dial | | | |
| DDC-6-220 | 6-Station, Indoor, 220 VAC Plug-In Transformer, Exclusive Digital Dial | | | |
| DDC-8-220 | 8-Station, Indoor, 220 VAC Plug-In Transformer, Exclusive Digital Dial | | | |
| OUTDOOR DIGITAL DIAL CONTROLLERS | | | | |
| DDC-4-220-0D | 4-Station, Outdoor, 220 VAC, Exclusive Digital Dial | | | |
| DDC-6-220-0D | 6-Station, Outdoor, 220 VAC, Exclusive Digital Dial | | | |
| DDC-8-220-0D | 8-Station, Outdoor, 220 VAC, Exclusive Digital Dial | | | |

Specifying Information — DDC™ Series

| DDC-X-XXX-XX | | | | | |
|-------------------------------|--|---------------|---|--|--|
| Description | Stations | Power Supply | Cabinet | | |
| LMII | X | XXX | XX | | |
| DDC - Digital Dial Controller | 4—4 Stations 6—6 Stations 8—8 Stations | 220 — 220 VAC | (blank) — Indoor AC Model OD — Outdoor AC Model* | | |
| Fxample: An 8- sta | tion indoor DDC controller with 220 | | _i | | |